



SURE-CLEAN PORCELAIN & STONE CLEANER



Sure-Clean Porcelain and Stone Cleaner was specifically developed to dissolve waxes and grout residue from the surface of porcelain tiles and other stone surfaces. Because it contains no acid, it can be safely used on all highly polished and unpolished surfaces. It is a surface preparation only and therefore, does not penetrate and weaken the masonry substrate as do powerful acids, nor is it capable of burning porcelain tile floors.

Most manufacturers ship their porcelain tiles with a coating to insure non-staining in transit. The coating materials can vary from waxes to polystyrene packaging. These coatings must be removed. Our cleaner has been designed to clean and restore porcelain tile in a single application. Unlike cleaners containing acids, this product dissolves waxes and grout residue without harming the tile or grout.

It is safe and effective to use on any surfaces--wall and floor. Sure-Clean Porcelain and Stone Cleaner is ready to use, and should not be diluted. Simply apply to the surface, agitate and wipe off.

Application: Sweep, dust, mop or vacuum the area to be treated to remove dust, loose soil and debris. Shake well. **FOR CLEANING SMALL AREAS:** Wet the area with a damp mop. Apply Sure-Clean Porcelain & Stone Cleaner to floor area. Agitate in a circular motion with a damp abrasive pad before it dries. Vigorously wipe over the surface with a clean terrycloth towel. **FOR CLEANING LARGE AREAS.** Use of a mechanical buffing machine is recommended. Wet the area with a damp mop. Apply Sure-Clean Porcelain & Stone Cleaner to floor area and agitate the cleaner in a circular motion with a white or brown polishing pad before it dries. A terry cloth or a clean white pad should then be used to buff and dry the surface. Remove dust by vacuuming then a light wash is recommended to remove any excess or haze from the surface. Do not fan or force dry.

To Seal the Surface after Cleaning: We recommend the application of Seal-Guard® Impregnator for Porcelain and Stone. Apply the first coat of Seal-Guard® Impregnator for Porcelain and Stone and allow to dry for a minimum of 5 hours. Apply a second coat of Seal-Guard® Impregnator for Porcelain and Stone and buff off prior to second coat drying completely. On small areas, use a soft rag to buff. For larger areas, use a wool or white polishing pad with buffing machine. Consult label directions for more complete instructions.

Specifications:

UN Number: Not Applicable

Transport: Not classified for transport – no transport warning sign required.

Appearance: An opaque liquid with a floral fragrance.

pH-Value, Conc. Solution: 10.50



Packaging: Available in 1 litre containers (6 x 1 litres to a case).

Coverage: 25 - 50 sq. metres per litre depending on the condition of the surface, method of application, material to be treated and quantity and type of soiling.

Storage/Shelf Life: Keep in sealed containers in a cool dry place. When properly stored, shelf life is indefinite.

Warranty: Sure-Clean for Porcelain and Stone is warranted against product defects and workmanship. If not completely satisfied with product performance, when used as directed, contact UK distributor for product replacement or refund of purchase price upon return of unused portion. Replacement cost for labor and installation materials such as tile are excluded. Any variance from the terms, misuse or misapplication of the product shall void and nullify this warranty.

Note: Consult the Sure-Clean Porcelain and Stone Cleaner Material Safety Data Sheet for details regarding Hazardous Properties and Personal Protective Equipment requirements.

Manufactured by: Seal-Guard Sealants (UK) Ltd., Ashcombe House, 5 The Crescent, Leatherhead, Surrey KT 22 8 DY, UK. See www.seal-guard.eu

Distributed in GB by:

Seal Britannia Ltd, The Barn, Park Leys, Botolph Claydon, Buckingham, Bucks
England MK18 2LR. Telephone: 0800 046 7941 Fax: 0844 811 1246
Email: admin@seal-guard.co.uk