

Seal-Guard[®] Impregnator Gold Label Penetrating Sealer For Grout, Tile & Masonry

This Penetrating Sealer for Grout, Tile and Masonry surfaces is a quick drying Impregnator in liquid form using same formulation as the award-winning aerosol. Suitable for all types of tile and masonry surfaces, including grout (damp/wet or dry), quarry tile, sandstone, terra cotta, limestone, stucco, concrete, porcelain, marble and granite. Helps protect treated surface against oil and water-based stains.

Installation:

Use as is. Test in obscure area to determine suitability for the intended use. Surface should be clean, dry, and free from any waxes, coatings, finishes or grouting materials. Protect any painted or stained surface adjacent to application area. Apply to surface in a thin, even coat with a pump or airless sprayer, brush, rag, mop or roller. One coat is normally sufficient, but a second application is recommended on more porous surfaces, i.e. terra cotta and sandstone, or heavy walkway areas to ensure complete protection. Allow twenty minutes between coats. Drying and curing time on a treated surface is approximately 2 1/2 hours, but for optimum results, the treated area should be kept dry and free from soils for at least 24 hours.

Note: On highly polished surfaces, such as porcelain, marble or granite, two coats are recommended. On small areas, buff off before the second coat is dry. For larger areas, let it dry and cure for 24 hours. If necessary, any excess can be easily removed with a damp cloth or buff off.

Pre-Grout Sealer/Grout Release:

Seal-Guard[®] can be used as a grout release prior to grouting to prevent grout stains and facilitate grout cleanup on porcelain tiles or other porous tiles.

Maintenance:

To clean treated areas, simply use water and mild detergent. There is no need to use harsh cleaning agents such as abrasive powders, ammonia, acids or bleach.

Specifications:

Un Number:	1993	
ADR Class:	3	



Appearance:	Clear, colorless, thin liquid with a characteristic odour	
Density (SG):	0.730 kg/litre @ 25 deg. C	
Quantities:	Available in 1 litre, 5 litres, 20 litre drums and 200 litre drums. 6 x 1 litres to a case and 4 x 5 litres to a case.	

Manufactured by: Seal-Guard Sealants (UK) Ltd., Ashcombe House, 5 The Crescent, Leatherhead, Surrey KT 22 8 DY, UK. See <u>www.seal-guard.eu</u>

Distributed in GB by:

Seal Britannia Ltd, The Barn, Park Leys, Botolph Claydon, Buckingham, Bucks England MK18 2LR. Telephone: 0800 046 7941 Fax: 0844 811 1246 Email: admin@seal-guard.co.uk